

Sizes for Storm-Tite 2013

*This non-leaking screw is suitable for fixing nearly all roofing profiles on crest or valley into steel battens or purlins up to 3mm thick (or 6mm mild steel) Lubrication is recommended. Using a drill on impact will render the corrosion warranty 'Null & Void' Drill Speed 2000 rpm plus.

Storm-Tite Cyclonic Steel Drilling Screw with seal						
Code	Point	Gauge	TPI	Length	Thread Length	Box QTY
C141025S4Z	Steel Drilling	14	10	25	10mm	750
C141050S4Z	Steel Drilling	14	10	50	35mm	500
C141060S4Z	Steel Drilling	14	10	60	42mm	500
C141070S4Z	Steel Drilling	14	10	70	50mm	400
C141080SAZ	Steel Drilling	14	10	80	70mm	400
C1410100S4Z	Steel Drilling	14	10	100	45mm	300
C1420125S4Z	Steel Drilling	14	20	125	80mm	250
C1420150S4Z	Steel Drilling	14	20	150	80mm	250
C1420175S4Z	Steel Drilling	14	20	175	90mm	200
C1420215S4Z	Steel Drilling	14	20	215	90mm	200
C1420250S4Z	Steel Drilling	14	20	250	90mm	150
C1420300S4Z	Steel Drilling	14	20	300	100mm	150
Storm-Tite Series 500 Steel Drilling *						
C1420125K4Z	K5	14	20	125	60mm	250
C1420150K4Z	K5	14	20	150	40mm	250
C1420200K4Z	K5	14	20	200	75mm	200
C1420225K4Z	K5	14	20	225	85mm	200
Storm-Tite -Dual Point Steel & Timber Drilling *						
C141065D4Z	Dual	14	10	65	50mm	500
C1414125D4Z	Dual	14	14	125	70mm	250
C1414150D4Z	Dual	14	14	150	70mm	250
C1410160D4Z	Dual	14	10	160	75mm	250
C1414175D4Z	Dual	14	14	175	70mm	200
C1414200D4Z	Dual	14	14	200	70mm	200
Storm-Tite T17 (Timber Drilling)						
C141050T4Z	Type 17	14	10	50	40mm	500
C141065T4Z	Type 17	14	10	65	55mm	500
C141075T4Z	Type 17	14	10	75	60mm	400
C1410100T4Z	Type 17	14	10	100	70mm	300
C1410125T4Z	Type 17	14	10	125	100mm	250
C1410135T4Z	Type 17	14	10	135	55mm	250
C1410150T4Z	Type 17	14	10	150	75mm	250
C1410200T4Z	Type 17	14	10	200	50mm	200
C1410250T4Z	Type 17	14	10	250	80mm	150
C1410300T4Z	Type 17	14	10	300	80mm	150
C1410350T4Z	Type 17	14	10	350	85mm	200

- Complies to AS/NZS 1170.2
- Low-High-Low sequence to BCA 2008 Spec.B1.2 by Branz Testing Report No. ST0781 Dated 13.3.09

Designed and Made in Australia for Australian Conditions

www.actionfasteners.com.au